

Digital Transformer Ratiometer DTR® Model 8510



DataView® is included with Model 8510



Features

- Measures power transformers, VT/PTs and current transformer CT turns ratios
- Displays turn ratio, excitation current, winding polarity and % deviation from the nameplate values
- Universal voltage (90-240V supply, 50-60Hz) via external smart/fast battery charger; complete charge in less than 4 hours
- Internal NiMH battery packs provide up to 10 hours of continuous operation
- Tests performed by exciting the primary and reading the secondary; provides safer conditions for the operator
- Display warns of incorrect lead connection, reverse polarity, open and short circuits
- Easy connection and test setup; no calibration or balancing required
- Large dual display with adjustable contrast ensures clearer visibility in any lighting environment day or night
- Low battery indicator
- Includes 15 foot lead set and soft carrying bag
- Stores up to 10,000 test results in internal memory
- USB port facilitates configuring the instrument and downloading test results
- Includes DataView® analysis software for programming, downloading, storing and report generation of test data
- EN 61010-1; 50V CAT IV

SPECIFICATIONS

MODEL	DTR® 8510
VT/PT Ratio Range	Auto-Ranging 0.8000:1 to 8000:1
CT Ratio Range	Auto-Ranging 0.8000 to 1000.0
Accuracy*	Ratio <10 to 1: ±0.2% of Reading Ratio 0 to 1000 to 1: ±0.1% of Reading Ratio >1000 to 1: ±0.2% of Reading Ratio 5000 to 8000.0: ±0.25% of Reading
Excitation Signal	VT/PT Mode: 32Vrms maximum CT Mode: 0 to 1A Auto Level, 0.1 to 5Vrms max.
Excitation Current Display	Range: 0 to 1000mA; Accuracy: ±2% of Reading ± 2mA
Excitation Frequency	70Hz
Measurement Method	In accordance with ANSI/IEEE C57.12.90™-2006
Display	LCD 16 character, 2 line, large format, LED backlight, day/night visible
Languages Supported	English, Spanish, French, Italian, German, Portuguese
Communication	Optically isolated USB 2.0
Data Storage	Stores up to 10,000 complete measurements
Power Source	Rechargeable 12V NiMH battery (included)
External Charger	90/240V, 50/60Hz (smart charger)
Battery Life	Up to 10 hours continuous operation; May not be used while recharging; Low battery LED/LCD indication
Charging Time	<4 hours

*23°C ± 5°C, 50 to 70% RH, full battery charge, no external fields or noise.

CATALOG NO. DESCRIPTION

2136.50	Digital Transformer Ratiometer DTR® Model 8510
Accessories (Optional)	
2136.76	Lead-Set of 2, 30 ft for use with DTR® Models 8500 & 8510
2136.77	Lead-Replacement set of 2, 15 ft for use with DTR® Models 8500 & 8510